



GE Fanuc Automation

QuickPanel™ Operator Interfaces

Available in a variety of sizes and display types, the best-selling family of QuickPanel™ touch screens goes where you want them to go. These rugged OI panels connect easily to all major PLCs and PLC networks, providing an information-rich, graphical interface wherever you need it. Compact, slim-profile QuickPanels replace a variety of discrete components, from push-buttons and pilot lights to message displays, significantly reducing installation and maintenance costs.



The QuickPanel Advantage


QuickPanels are the most complete family of operator interface products available. Advantages include:

- Broad range of display sizes from 5" to 12"
- Choice of color or monochrome units
- Cost-effective replacement for thousands of discrete components
- Communication with over 70 PLCs
- Communication over Serial networks, Open Device networks, and Ethernet networks
- UL Class I, Division 2 and CE marked (some 24 VDC models)
- Industrially hardened NEMA 4X/12 for demanding factory floor environments
- Single configuration editor to save hours of programming time
- QuickDesigner - a Windows®-based graphical editor with intuitive drag-and-drop functionality
- Integration with CIMPLICITY® Machine Edition as part of a complete development environment—increased functionality for more complex applications
- Dynamic graphics including trend, alarm and operator message displays
- Global network of sales support and distribution channels
- 2-year warranty on all models
- Miniscule failure rate with over 450,000 units installed globally



QuickPanel Family

From the QuickPanel Mini up to the most advanced QuickPanel, user-friendly QuickDesigner programs them all. Or, for increased functionality and the added benefits of an integrated development environment, choose CIMPLICITY Machine Edition.



	QuickPanel Mini	QuickPanel, Jr.	QuickPanel, Jr.	QuickPanel	QuickPanel	QuickPanel	QuickPanel
Display Size	6"	5"	6"	7.5"	9"	10.5"	12.1"
Display Type	Blue Mono	Mono or STN LCD	Mono, STN or TFT LCD	TFT	ElectroLuminescent	Mono, STN or TFT LCD	TFT LCD
Display Resolution	320 x 240	320 x 240	320 x 240	640 x 480	640 x 480	640 x 480	800 x 600
Memory	1MB	256K	1 MB	4 MB	2 MB	2 MB	2 MB
Size (HxWxD in)	6.3 x 8.3 x 2.25	5 x 6.75 x 2.125	5.4 x 6.7 x 2.25	6.7 x 8.5 x 2.4	8.5 x 10.8 x 1.9	9.5 x 12.5 x 3	10.7 x 13.6 x 3.2
Voltage	20.4 - 27.6 VDC	20.4 - 27.6 VDC	20.4 - 27.6 VDC	19.2 - 28.8 VDC	20.4 - 27.6 VDC	20.4 - 27.6 VDC	20.4 - 27.6 VDC
					85 - 132 VAC	85 - 132 VAC	85 - 132 VAC
Power	12 Watts	15 Watts	15 Watts	28 Watts	50 Watts	50 Watts	50 Watts
Operating Temp	0° to 50° C	0° to 45° C	0° to 45° C	0° to 50° C	0° to 50° C	0° to 45° C	0° to 40° C
Storage Temp	-20° to 60° C	-20° to 60° C	-20° to 60° C	-20° to 60° C	-10° to 60° C	-10° to 60° C	-10° to 60° C



GE Fanuc Automation

GE Fanuc Automation Information Centers

USA and the Americas 1-800-GE FANUC or (434) 978-5100

Europe and Middle East (352) 727979-1

Asia Pacific 86-21-3222-4555

© 2003 GE Fanuc Automation Americas, Inc. All Rights Reserved. QuickPanel is a trademark and Genius is a registered trademark of GE Fanuc Automation Americas, Inc. Windows is a registered trademark of Microsoft Corporation. All other trademarks and registered trademarks are the property of their respective owners.

Additional Resources

For detailed technical specifications and product ordering information, please visit the GE Fanuc website at:

www.gefanuc.com